

## INTERNATIONAL COOPERATION TREATY

PCT

## NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

Commissioner  
 US Department of Commerce  
 United States Patent and Trademark  
 Office, PCT  
 2011 South Clark Place Room  
 CP2/5C24  
 Arlington, VA 22202  
 ETATS-UNIS D'AMERIQUE  
 in its capacity as elected Office

<b>Date of mailing (day/month/year)</b> 26 June 2001 (26.06.01)	<b>Applicant's or agent's file reference</b> IREA0008P
<b>International application No.</b> PCT/US00/22476	<b>Priority date (day/month/year)</b> 16 August 1999 (16.08.99)
<b>International filing date (day/month/year)</b> 16 August 2000 (16.08.00)	
<b>Applicant</b> JOHNSON, Michael, W. et al	

1. The designated Office is hereby notified of its election made:

☒ in the demand filed with the International Preliminary Examining Authority on:  
 21 February 2001 (21.02.01)

☐ in a notice effecting later election filed with the International Bureau on:  
 \_\_\_\_\_

2. The election ☒ was  
☐ was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

<b>The International Bureau of WIPO</b> 34, chemin des Colombettes 1211 Geneva 20, Switzerland Facsimile No.: (41-22) 740.14.35	<b>Authorized officer</b> CROCI Christelle Telephone No.: (41-22) 338.83.38
--	---

***This Page Blank (uspto)***

(19) World Intellectual Property Organization  
International Bureau



10/049972

(43) International Publication Date  
22 February 2001 (22.02.2001)

PCT

(10) International Publication Number  
WO 01/013583 A3

- (51) International Patent Classification<sup>7</sup>: H04L 12/28, 29/06, H04M 11/06
- (21) International Application Number: PCT/US00/22476
- (22) International Filing Date: 16 August 2000 (16.08.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/149,214 16 August 1999 (16.08.1999) US
- (71) Applicant (for all designated States except US): IREADY CORPORATION [US/US]; Suite 200, 2903 Bunker Hill Lane, Santa Clara, CA 95054 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): JOHNSON, Michael, W. [US/US]; 437 Ely Road North, Petaluma, CA 94954 (US). MINAMI, John, S. [US/US]; Suite 428, 330 Elan Village Lane, San Jose, CA 95134 (US). Koyama, Ryo [JP/US]; 343 Hawthorne, Palo Alto, CA 94301 (US).
- (74) Agents: GLENN, Michael et al.; Glenn Patent Group, Suite L., 3475 Edison Way, Menlo Park, CA 94025 (US).
- (81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

RECEIVED


with international search report

NOV 04 2002

[Continued on next page]

(54) Title: INTERNET JACK

Technology Center 2100



(57) Abstract: The claimed invention herein provides a simple, economical, and safe way to connect a new class of Internet-ready devices and appliances to the Internet without the use of a personal computer (PC). The claimed invention herein provides an Internet dial-tone, so to speak, to applications ranging from toys and entertainment consoles to electronic books and health equipment just as a traditional telephone jack provides a plain old telephone system (POTS) dial-tone for phones, modems, and fax machines. The invention herein features a modem, network stack, and application protocols alleviating the need for sophisticated logic within attached devices. With one-touch, appliances can quickly and easily connect to the Internet.

WO 01/013583 A3

**This Page Blank (uspto)**



(88) Date of publication of the international search report:  
12 September 2002

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**This Page Blank (uspto)**

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
22 February 2001 (22.02.2001)

PCT

(10) International Publication Number  
WO 01/13583 A2

(51) International Patent Classification<sup>7</sup>: H04L 12/28

(21) International Application Number: PCT/US00/22476

(22) International Filing Date: 16 August 2000 (16.08.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/149,214 16 August 1999 (16.08.1999) US

(71) Applicant (for all designated States except US): IREADY CORPORATION [US/US]; Suite 200, 2903 Bunker Hill Lane, Santa Clara, CA 95054 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): JOHNSON, Michael, W. [US/US]; 437 Ely Road North, Petaluma, CA 94954 (US). MINAMI, John, S. [US/US]; Suite 428, 330

Elan Village Lane, San Jose, CA 95134 (US). KOYAMA, Ryo [JP/US]; 343 Hawthorne, Palo Alto, CA 94301 (US). GENTRY, Landon [US/US]; 545 Tucker Road, Scotts Valley, CA 95066 (US).


(74) Agents: GLENN, Michael et al.; Glenn Patent Group, Suite L., 3475 Edison Way, Menlo Park, CA 94025 (US).

(81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

[Continued on next page]

(54) Title: INTERNET JACK



(57) Abstract: The claimed invention herein provides a simple, economical, and safe way to connect a new class of Internet-ready devices and appliances to the Internet without the use of a personal computer (PC). The claimed invention herein provides an Internet dial-tone, so to speak, to applications ranging from toys and entertainment consoles to electronic books and health equipment just as a traditional telephone jack provides a plain old telephone system (POTS) dial-tone for phones, modems, and fax machines. The invention herein features a modem, network stack, and application protocols alleviating the need for sophisticated logic within attached devices. With one-touch, appliances can quickly and easily connect to the Internet.

WO 01/13583 A2



IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *Without international search report and to be republished upon receipt of that report.*



# Internet Jack

## BACKGROUND OF THE INVENTION

5

### TECHNICAL FIELD

The present invention relates to Internet connections. More particularly, the present invention relates to a new connection platform for connecting to the Internet that provides an ease of use to a user as does a phone jack.

### DESCRIPTION OF THE PRIOR ART

#### Internet Appliances vs. Internet-ready Appliances

Internet appliances already appear in the form of Web enabled televisions, screen phones, Web Tablets, and Email Readers, that take advantage of the Internet to send and receive data, browse Web sites, and other computer-type activities. Internet appliances may be characterized as requiring an Internet connection for primary usage, or as being permanently attached to an Internet link. In the latter case, the device may not need to be on-line continuously, but might always be attached to a phone jack or to some other Internet connection.

A new class of devices will soon emerge that will use the Internet to simply augment primary functions, and that will not require a permanent hook up to an Internet link nor will even require the Internet to function. Of such herein cited portable and/or Internet optional function devices (herein referred to interchangeably as Internet-ready devices or appliances), connection is required only when updating, sending, or receiving information. Internet-ready device categories may include, but are not limited to, toys, electronic books, personal health monitors, and MP-3 players, for example. A child's toy

or an electronic book may need only to connect to a specific Web site when downloading new content. After downloading the content, the device may be taken anywhere to be played with or used. Other devices such as digital cameras may need only to be connected when sending pictures to a photo-developing center, to relatives, or to remote displays.

A notable characteristic of Internet-ready devices is that they are all mass market consumer electronic type products, and as such have very real cost and price constraints. It is noted that embedding necessary logic to connect a device to the Internet means adding a modem, a CPU, a network stack, memory, and miscellaneous glue logic to the device. While the costs of adding such components are decreasing, for example, adding \$10 - \$20 in parts, it is noted that adding such cost to a device selling for \$25 is probably not practical.

15

#### Using the PC as the Connection

Today the PC is used as an interfacing device for the new class of Internet-ready appliances. The percentage of households owning PC's continues to grow, making a PC a more prevalent platform on which to base a solution. An Internet enabled PC will already have a modem installed, along with a powerful processor, advanced operating system, and more than sufficient memory. The PC can easily accept new software drivers to communicate to attached devices, through serial ports, parallel ports, USB's, 1394's, or any other input-output (I/O) bus structure. However, there are many well-documented problems with the solution of using PC's as the connection, such problems including ease of use, cost, and security. These issues make the PC an expensive and cumbersome solution at best, and an intimidating and adoption hindrance in the worst case.

A computer, with all of the advances in technology, is the most sophisticated and technically complicated product in many households. Installing device drivers, successfully attaching an appliance, and configuring network

connections are not for the faint of heart, and certainly not for the typical consumer electronics user. While driver installation is automated in recent releases, resolving driver conflicts and configuring parameters is not a task with which most users can cope. If an Internet-ready device is a child's toy, 5 the process described herein above would most likely require adult supervision or visa-versa in many homes. Therefore, the process may be one that could not be performed by anyone. Techno-phobia may be enough to keep the solution of installing device drivers, successfully attaching an appliance, and configuring network connections from becoming the one of 10 choice.

Cost is another major concern with using the PC as the connection platform. While a more than capable PC can be obtained for well under \$1000 today, the price tag is still beyond the point where people can afford to put one in 15 every room of the house. Clearly, a proper solution is one in which the price of the connection feature makes it possible for homes to have multiple ports. The price of a telephone is a good analogy. When the cost of a phone was relatively high, most families had one phone centrally located within the home. As the cost of a phone dropped, people began putting one in every bedroom, 20 the den, and even the bathroom.

Security and data integrity is another issue with using computers as the Internet connection platform. Various entry points in the upload and download process can be altered by users because the computer is not a closed 25 system, thereby possibly violating the intended use by manufacturers. Take, for example, imagining a parent's concern if adult audio clips are downloaded into talking toys, or if downloadable game consoles access unauthorized pirate sites. These are concerns that also worry manufacturers of Internet-ready appliances, because it's their image, reputation, and revenues that are 30 affected. Safe guards, such as, for example, the RSAC initiative, help in providing a process by which only intended content may be downloaded. However, this type of rating scheme depends upon compliant browsers and

upon proper browser setup to be effective. Also, such rating scheme cited herein above does not prevent a user from accessing unauthorized sites.

- Clearly, a new connection platform is needed to service the class of Internet-ready appliances. The new connection platform must meet required cost, security, and ease of use points that today are lacking in a computer oriented solution. At the same time the new connection platform must provide a standard connection port and must offer performance levels to which consumer electronic users have become accustomed. System crashes and long boot times are accepted behaviors in a PC world, however, are causes for product returns for normal personal electronics. It would therefore be advantageous to provide a preferred solution that is as stable as a television, and as cost affordable as a telephone.
- 15 It would be advantageous to provide a new connection platform that makes it possible to have such a new connection platform for each possible Internet connection point in the home, whether the possible Internet connection point is a telephone jack, cable connection, or other means.
- 20 It would be advantageous to provide a new connection platform system that is closed. That is, at no point does a user have to intervene or provide any additional information. When such a system is closed, the Internet connection only goes to the site specified by the appliance.
- 25 It is noted that the prior art is using PC's as the connection to the Internet.
- It is also noted that prior art combines Internet related components into one device, such as, for example, the Web TV box that contains, but is not limited to, a modem, protocol handler, network stack, Internet interface and telephone interface.
- 30

## **SUMMARY OF THE INVENTION**

The claimed invention herein provides a simple, economical, and safe way to connect a new class of Internet-ready devices and appliances to the Internet without the use of a personal computer (PC). The claimed invention herein provides an Internet dial-tone, so to speak, to applications ranging from toys and entertainment consoles to electronic books and health equipment just as a traditional telephone jack provides a plain old telephone system (POTS) dial-tone for phones, modems, and fax machines. The invention herein features a modem, network stack, and application protocols alleviating the need for sophisticated logic within attached devices. With one-touch, appliances can quickly and easily connect to the Internet.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

15

Fig. 1 is a block diagram of a preferred embodiment of the claimed invention herein showing the invention for a telephone connection;

20

Fig. 2 shows a schematic diagram of a device using the Internet jack according to the invention;

Fig. 3 shows a schematic diagram of a device using the Internet jack according to the invention;

25

Fig. 4 is a block diagram showing a preferred embodiment of logical blocks according to the invention; and

30

Fig. 5 shows a schematic diagram of another embodiment of the invention in which a raw socket is used directly.

## DETAILED DESCRIPTION OF THE INVENTION

The claimed invention herein provides a simple, economical, and safe way to connect a new class of Internet-ready devices and appliances to the Internet without the use of a personal computer (PC). The claimed invention herein provides an Internet dial-tone, so to speak, to applications ranging from toys and entertainment consoles to electronic books and health equipment just as a traditional telephone jack provides a plain old telephone system (POTS) dial-tone for phones, modems, and fax machines. The invention herein features a modem, network stack, and application protocols alleviating the need for sophisticated logic within attached devices. With one-touch, appliances can quickly and easily connect to the Internet.

### The Internet Jack

The claimed invention herein, also referred to herein as an Internet Jack, fulfills the need for a new connection platform discussed herein above in the Background section. The invention is generic enough to support a wide variety of devices from entertainment products to health equipment. Using the invention, any device requiring Internet connectivity is able to plug into an Internet Jack just as any device requiring power may be plugged into an AC outlet. The Internet Jack provides an Internet dial tone that furnishes a well-defined set of features and/or services and is similar to a telephone or cable TV jack. These services include, but are not limited to, providing a platform for Internet connectivity, all network protocol processing, and standard data decoding. Because these services are provided in a separate jack that can be used by a multitude and variety of products, the added cost of providing these services are removed from Internet-ready appliances. Therefore, adding such services and/or features through the claimed invention is much more practical and economical for mainstream consumer electronic products, than adding them to the products themselves.

The preferred embodiment the invention has a minimum of two connection ports. One port attaches to a telephone or other Internet conduit. The second port is used for any Internet-ready device to attach. A simple one-touch operation allows a user to easily connect the device to the Internet, and thereby retrieve or send data. An indicator is provided on the claimed invention to inform the user when the desired operation is complete. Because the invention is designed for the purpose of providing Internet connectivity for this new class of Internet-ready appliances, its user interface is streamlined in such a way that any person familiar with plugging in electronic products into wall outlets can perform the operation. Display indicators on the invention can range, for example, from simple light emitting diodes (LED's) to small liquid crystal displays (LCD) screens that inform users on the status of operations. Ease of use is a main design criterion of the invention.

Fig. 1 is a block diagram of a preferred embodiment of the claimed invention herein showing the invention for a telephone connection. The invention 100 connects to a standard telephone jack 110 by a connection 106 from a telephone front end logical component 105, provides a plug 107 for a telephone 120 from the telephone front end logical component 105, and a connection 108 to an Internet-ready device from an Internet jack interface logical component 101 of the invention 100. A data modem logical component 104 is provided. The data modem 104 used in the preferred embodiment ranges from 2400 bps to 56 kbps, and to xDSL and cable modems, depending on desired performance level and cost target of the invention. A network stack logical component 103 is provided. In the preferred embodiment it handles all TCP/IP and data link layer protocols needed for Internet connectivity. A protocol handler logical component 102 is provided that, in the preferred embodiment, provides built in support for POP3, SMTP, FTP, and HTTP. These protocols cited herein are standard methods by which data is transferred over the Internet today. In addition to these protocols, the invention herein 100 provides DNS support for resolving server names and URL's and DHCP or other boot protocols for use where the

Internet jack resides on a broadband connection. The Internet jack interface block 101 handles communication with Internet-ready devices.

5 In the preferred embodiment, total silicon cost for the claimed invention ranges from under \$10 on up depending on modem type used and other features incorporated into the device. The invention is thereby cost affordable to build as a standalone device or to embed into other devices that attach to telephone jacks, for example.

10 It is noted that with new Internet capable phones, answering machines, and fax machines, and the like, the cost of adding an Internet jack is almost negligible because such devices already contain the modem and network stack blocks. Furthermore, most of these devices also include protocol support, so that the only additional cost is for the Internet jack interface and  
15 physical connector for Internet-ready devices. Therefore, the added cost of an Internet jack to such devices is under one dollar.

It is noted that other physical Internet connections, such as, for example, cable modems can also be supported. The claimed invention can easily be  
20 added to, for example, STB's, Ethernet hubs, or other hubs that attach to any of the new home networking standards.

In the latter scenario described herein above, in another preferred embodiment, the Internet jack is a standalone device having a network  
25 connection on one end, and an Internet-ready device connector on the other. This implementation is depicted in Fig. 2. The Internet 200 is connected to a Gateway 210 that is connected to a home network 230. Connected to the home network 230 are N PC's 240, an Internet appliance 250 and the Internet  
jack 260. Connected to the Internet jack is an Internet-ready device 270.

30

It is noted that examples of a home network 230 include, but are not limited to, a standard Ethernet, telephone line, electrical outlines, and wireless



means. Examples of an Internet appliance 250 include, but are by no means limited to, Web TV box, email, and a telephone.

It is noted that in the preferred embodiment, the claimed invention is a closed system that thereby provides additional advantage. As an example, an Internet-ready device provides information such as a URL or mail server name to the Internet jack. The Internet jack connects and then retrieves or sends the information. At no point does the user need to intervene or provide additional information. Also because the system is closed, the Internet connection only goes to the site specified by the appliance.

In one embodiment, a closed system such as described herein above uses a rating system, such as, for example, RSAC effectively on retrieved data. That is, all data must pass through the Internet jack prior to being downloaded to the Internet-ready device. In scenarios where a rating is used, the device would pass a rating level along with the target URL, mail server, or the like. Once data is retrieved from the target URL, mail server, or the like, it is filtered by the Internet jack, whereupon the Internet jack only passes along such data to the Internet-ready appliance if the data does not exceed the stated rating level.

In other embodiments, other security schemes are implemented to prevent accessing information on unauthorized sites. In this situation and in one embodiment, a key code is passed from the device to an Internet site, which then uses a pre-agreed upon algorithm to generate a response. This response is then sent back to the device thus authenticating the site to the device. This same mechanism can be used in the reverse path to prevent unauthorized devices from accessing a particular site.

#### 30 Example 1: the Talking Toy

Fig. 3 shows a schematic diagram of a device using the Internet jack according to the invention. The Internet-ready device is a child's talking toy

300 using the Internet jack 310. Instead of being limited to the sounds shipped with the toy, technology now allows a child to update new sounds from a manufacturer's Internet site 330 through the Internet 320. The toy 300 is plugged into the Internet jack 310. The user presses a button 311 on the  
5 Internet jack 310. The Internet button on the connection platform 310 then initiates communication between the Internet jack 310 and the toy 300. Specifically, in this embodiment, an announcement byte is sent to the toy 300 from the jack 310. In response the toy 300 sends to the jack 310 a manufacturer's POP server for that particular toy. The Internet jack 310 then  
10 connects to the Internet 320, initiates a POP connection to the specified server 330, and retrieves an email message.

In this embodiment, the manufacturer's Internet site 330 is required only to keep one email message in the account, the message conveying the latest  
15 sound bytes for the toy. Examples of latest sounds bytes include, but are not limited to, sounds associated with seasonal events such as, for example, holidays, or sounds associated with media, such as, for example, television programs or movie releases. When the sounds file is downloaded onto the Internet jack 310, it is parsed by the jack 310. A typical example of the sound  
20 file is a .wav file. The data is decoded by the jack 310 and sent to the toy 300. Typically, for example, the Internet jack 310 strips headers and the like from the file sent by the manufacture's site 330, and only sends the a pure sound file, or .wav file, to the toy 300.

25 The Internet jack 310 is not required to understand the data because the only service it provides in this situation is to pass requested data to the toy 300. It is the toy that determines the data as new sound data. The toy stores and processes the data accordingly. The toy 300 is required only to have capabilities to communicate with the Internet jack 310 and to store new  
30 information it receives. The toy is not required to have any network protocol knowledge or modem capabilities. Therefore, manufacturers can incorporate Internet jack connectivity and usage into products of all price ranges.

### Example 2: the Electronic Book

The electronic book is another example of an Internet-ready device. By connecting the electronic book to an Internet jack a user can download new content for the book without using or being required to use a computer. In this example the book provides a URL to the Internet jack. Once a connection is established the requested HTML page is downloaded and sent to the electronic book. Because the Internet-ready device contains an LCD screen, the device displays a list of books from which the user may select. The user selects a choice that causes the device to send to the Internet jack another URL. Requested data is then retrieved and delivered to the electronic book. HTTP can also be used to post credit card information or account numbers for billing purposes. If the electronic book is for a general reader, the book may not have any rating restrictions. However, in cases when the book is a child's book the book may provide along with the target URL a rating level that reflects the level of information it can accept. The resulting downloaded HTML data is then parsed. The ratings tag is checked prior to sending the downloaded requested information to the electronic book.

Fig. 4 is a block diagram showing a preferred embodiment of logical blocks according to the invention. A user interface logical block 400 is connected to a micro controller logical block 410. The user interface logical block 400 supports, for example, a display or a keypad, and the like. The micro controller logical block 410 performs such functionality as, for example, parsing and decoding. The micro controller logical block 410 is connected to an application protocols logical block 420. Examples of protocols supported by this block 420 are, but are not limited to, HTTP and POP. The application protocols logical block 420 is connected to a network stack 430. The network stack 430 supports such protocols as but is not limited to, for example, TCT and IP. The network stack 430 is connected to a physical connection logical block 440 that provides but is not limited to, for example, modem support and the Ethernet. The physical connection logical block 440 is connected by a

port 441 to the Internet 450. Similarly, the micro controller logical block 410 is connected by a serial port 411 to a client's Internet-ready device 460, such as, for example, a toy.

- 5 It is noted that the logical blocks can be implemented in hardware or software.

Another embodiment comprises the same components as in Fig. 4, but omits the user interface logical block 400.

- 10 It is noted that the preferred embodiment depicted by Fig. 4 is by no means limited by the limitations of contemporary technological limitations and can be adapted to accommodate technological advances of the future.

#### Other Devices

- 15 In another embodiment, along with provided protocols a raw socket interface is also supported by the claimed invention herein. The raw socket feature allows Internet-ready devices to use protocols, such as, for example, Telnet and RSH that are not necessarily natively supplied by the Internet jack.
- 20 When using a raw socket interface, the Internet-ready device supplies information such as, for example, a type of connection requested, such as, for example, TCP/UDP, the target Internet site, such as, for example, a server name, URL, or IP address, and target port number. Any data received by the raw socket connection is passed to the attached Internet-ready device. This
- 25 operation mode is optional and is not needed for simpler applications.

- Fig. 5 shows a schematic diagram of another embodiment of the invention depicted in Fig. 4 in which a raw socket is used directly. The user interface logical block 400 is connected to the micro controller logical block 410. The
- 30 micro controller logical block 410 connects directly to a raw socket layer 520. The raw socket layer 520 is connected to the network stack 430. The network stack 430 is connected to the physical connection logical block 440. The

- physical connection logical block 440 is connected by a port 441 to the Internet 450. The micro controller logical block 410 is connected by the serial port 411 to a client's Internet-ready device 560 that requires a special protocol, such as, for example, Telnet, a proprietary protocol, or any standard protocol not provided by the Internet jack's application protocols.

#### Internet Jack Feature Specifications

Table A herein below provides a summary of features provided by the preferred embodiment of the Internet jack invention claimed herein.

10

Table A

FEATURE	COMMENT
Full TCP/IP network stack included	
Supported Application Protocols <ul style="list-style-type: none"> <li>• POP3</li> <li>• SMTP</li> <li>• HTTP</li> <li>• DNS</li> <li>• FTP</li> <li>• DHCP</li> </ul>	
Raw Socket Support <ul style="list-style-type: none"> <li>• 4 sockets</li> <li>• Ability to set target and source port numbers</li> <li>• TCP or UDP transport layers</li> </ul>	
Internet Connection independent	Will work with telephone modems, cable modems, Ethernet, etc.
Low Cost	
Base64 and Quoted Printable data decoding	
Simple "One-Touch" operation	
Built in RSAC support	

Will support multiple Internet-Ready device connectors	It is expected that along with RS-232, IR and other connector types will be made available.
Auto BAUD rate detection for RS-232 type connections	

### Summary

With the advent of Internet-ready devices, a solution to connect these appliances to the Internet in a cost-affordable, safe, and easy to use method is needed. The Internet jack invention claimed herein provides these cited advantages in a well-defined closed system. The Internet jack invention claimed herein is designed to address, among other concepts, a particular market need in a most manufacturer-friendly and user-friendly manner possible in the spirit of the concept that the consumer electronics world is dominated by point solutions.

It is noted that the Internet jack invention does not preclude the use of the PC as a connection platform. The new connection platform claimed herein is compatible with the concept that it is expected that the PC can be used along with the Internet jack to provide a more feature-rich connection environment.

It is noted that communication protocol between Internet-ready devices and the Internet jack invention is the same as that between Internet-ready devices and a computer. Therefore, manufacturers are not required to build multiple versions or a variety of products to compensate for compatibility, wherein compatibility problems are due to specific products depending on specific connection platforms.

For example, citing the talking toy example herein above, a PC stores past files for reloading previous sound bytes. In another example, citing the electronic book example herein above, a PC stores a digital library. In

contrast, the Internet jack invention herein provides a simple alternative, low cost, secure, and easy to use substitute for applications that require a PC.

In conclusion, the claimed invention herein provides a solution to the problem  
5 of making the new class of Internet-ready appliances a reality because it incorporates necessary networking logic, thereby providing to the market a ubiquitous Internet dial-tone.

## CLAIMS

1. An apparatus for a user to connect an Internet-ready device to the  
5 Internet by an Internet connection independent means, comprising:  
at least two connection ports, wherein the first port connects to an  
Internet conduit, and the second port connects to said Internet-ready device;  
a user interface, allowing said user to initiate passing information  
between said Internet-ready device and said Internet, and having associated  
10 indicators to indicate to said user that said passing of information is complete;  
a protocol handler block for receiving and handling messages from said  
user interface and from said Internet-ready device, and for sending on said  
handled messages to a network stack block;  
said network stack block for handling an associated subset of said  
15 handled messages, and sending on to a physical connection block; and  
said physical connection block for connecting to said Internet.
2. The apparatus in Claim 1, wherein said indicators range from, but are  
not limited to, simple LED's to small LCD screens, cursor controls, and  
20 keyboards and/or keypads.
3. The apparatus in Claim 1, further comprising a standard telephone jack  
connection.
- 25 4. The apparatus in Claim 1, wherein said physical connection block  
comprises a data modem.
5. The apparatus of Claim 4, wherein said data modem ranges from 2400  
bps to 56 kbps, or wherein said data modem is an xDSL or cable modem.

30



6. The apparatus of Claim 1, wherein said network stack block handles all network, transport layer, and data link layer protocols needed for Internet connectivity.

5 7. The apparatus of Claim 1, wherein said protocol handler provides any of the following application protocols: POP3, SMTP, HTTP, FTP, and DNS.

8. The apparatus of Claim 1, whereby said apparatus is built as a standalone device.

10

9. The apparatus of Claim 1, whereby said apparatus is built to be embedded into other devices.

10. The apparatus of Claim 1, wherein said data modem is a cable  
15 modem.

11. The apparatus of Claim 1, added easily to any of, but not limited to:  
STB's;  
Ethernet hubs; and  
20 hubs that are attached to new home networking standards.

12. The apparatus of Claim 1, wherein said connection between said Internet-ready device and said Internet is closed in that said user never intervenes to provide additional information.

25

13. The apparatus of Claim 1, further comprising a rating system, wherein said Internet-ready device passes a rating level to the Internet, whereupon only data not violating said rating level is passed back to said Internet-ready device.

30

14. The apparatus of Claim 1, further comprising security schemes to prevent accessing information of unauthorized sites.

15. The apparatus of Claim 14, further comprising a key code for passing from said Internet-ready device to said Internet, whereupon a pre-agreed upon algorithm is used to generate a response, whereupon said response is  
5 sent back to said Internet-ready device, thereby authenticating said Internet connection to said Internet-ready device.

16. The apparatus of Claim 15, used in reverse to prevent unauthorized Internet-ready devices from accessing a particular site.

10

17. The apparatus of Claim 13, wherein said rating system is RSAC.

18. The apparatus of Claim 1, wherein said initiating passing information between said Internet-ready device and said Internet is by said user pressing  
15 a button, thereby providing a one-touch operation.

19. The apparatus of Claim 1, further comprising raw socket support.

20. The apparatus of Claim 19, wherein said raw socket support further  
20 comprises any of, but is not limited to:

support for multiple sockets;  
ability to set target and source port numbers; and  
TCP or UDP transport layers.

25

21. The apparatus of Claim 1, wherein said protocol handler comprises a  
micro controller.

22. The apparatus of Claim 21, wherein said micro controller provides  
30 Base64 and/or quoted printable data decoding.

23. The apparatus of Claim 21, wherein said micro controller communicates directly with said Internet-ready device and with a raw socket.
24. The apparatus of Claim 1, further comprising multiple Internet-ready  
5 device connectors.
25. The apparatus of Claim 1, further comprising auto BAUD rate detection for RS-232 type connections.
- 10 26. The apparatus of Claim 5, further comprising a pass through port whereby an existing POTS appliance may be connected.
27. A method for a user to connect an Internet-ready device to the Internet  
15 by an Internet connection independent means, comprising:
- providing at least two connection ports, wherein the first port connects to an Internet conduit, and the second port connects to said Internet-ready device;
  - providing a user interface, allowing said user to initiate passing  
20 information between said Internet-ready device and said Internet, and having associated indicators to indicate to said user that said passing of information is complete;
  - providing a protocol handler block for receiving and handling messages from said user interface and from said Internet-ready device, and for sending  
25 on said handled messages to a network stack block;
  - providing said network stack block for handling an associated subset of said handled messages, and sending on to a physical connection block; and
  - providing said physical connection block for connecting to said Internet.
- 30 28. The method in Claim 27, wherein said indicators range from, but are not limited to, simple LED's to small LCD screens, cursor controls, keypads and/or keyboards.

29. The method in Claim 27, further comprising providing a standard telephone jack connection.

5 30. The method in Claim 27, wherein said physical connection block comprises a data modem.

31. The method of Claim 30, wherein said data modem ranges from 2400 bps to 56 kbps, or wherein said data modem is an xDSL and cable modem.

10

32. The method of Claim 27, wherein said network stack block handles all network, transport layer, and data link layer protocols needed for Internet connectivity.

15 33. The method of Claim 27, wherein said protocol handler provides any of the following application protocols: POP3, SMTP, HTTP, FTP, and DNS.

34. The method of Claim 27, whereby standalone capability is provided.

20

35. The method of Claim 27, whereby embeddable capability into other devices is provided.

36. The method of Claim 27, wherein said data modem is a cable modem.

25

37. The method of Claim 27, further providing easy connectivity to any of, but not limited to:

STB's;

Ethernet hubs; and

30

hubs that are attached to new home networking standards.

38. The method of Claim 27, wherein said connection between said Internet-ready device and said Internet is closed in that said user never intervenes to provide additional information.
- 5 39. The method of Claim 27, further providing a rating system, wherein said Internet-ready device passes a rating level to the Internet, whereupon only data not violating said rating level is passed back to said Internet-ready device.
- 10 40. The method of Claim 27, further providing security schemes to prevent accessing information of unauthorized sites.
41. The method of Claim 40, further providing a key code for passing from said Internet-ready device to said Internet, whereupon a pre-agreed upon  
15 algorithm is used to generate a response, whereupon said response is sent back to said Internet-ready device, thereby authenticating said Internet connection to said Internet-ready device.
42. The method of Claim 41, used in reverse to prevent unauthorized  
20 Internet-ready devices from accessing a particular site.
43. The method of Claim 39, wherein said rating system is RSAC.
44. The method of Claim 27, wherein said initiating passing information  
25 between said Internet-ready device and said Internet is by said user pressing a button, thereby providing a one-touch operation.
45. The method of Claim 27, further providing raw socket support.
- 30 46. The method of Claim 45, wherein said raw socket support further comprises any of, but is not limited to:  
support for multiple sockets;

ability to set target and source port numbers; and  
TCP or UDP transport layers.

47. The method of Claim 27, wherein said protocol handler comprises a  
5 micro controller.

48. The method of Claim 47, wherein said micro controller provides  
Base64 and/or quoted printable data decoding.

10 49. The method of Claim 47, wherein said micro controller communicates  
directly with said Internet-ready device and with a raw socket.

50. The method of Claim 27, further providing multiple Internet-ready  
device connectors.

15 51. The method of Claim 27, further providing auto BAUD rate detection for  
RS-232 type connections.

52. An apparatus for a user to connect an Internet-ready device to the  
20 Internet, wherein said apparatus is embedded into said Internet-ready device,  
said apparatus comprising:

a user interface block to connect to said Internet-ready device; and  
a physical connector block for connecting to the said Internet.

25 53. The apparatus of Claim 52, further comprising a protocol handler block.

54. The apparatus of Claim 52, wherein said embeddable devices  
comprise any of, but are not limited to:

Internet capable phones;  
30 answering machines; and  
fax machines.

55. The apparatus of Claim 31, further comprising a pass through port whereby an existing POTS appliance may be connected.

1/3




FIG. 1




FIG. 2



2/3




FIG. 3




FIG. 4

3/3




FIG. 5

# PATENT COOPERATION TREATY

# PCT

## INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference <b>IREA0008P</b>	<b>FOR FURTHER ACTION</b> see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. <b>PCT/US 00/ 22476</b>	International filing date (day/month/year) <b>16/08/2000</b>	(Earliest) Priority Date (day/month/year) <b>16/08/1999</b>
Applicant  <b>IREADY CORPORATION et al.</b>		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 5 sheets.  
☐ It is also accompanied by a copy of each prior art document cited in this report.

**1. Basis of the report**

- a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.
- ☐ the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).
- b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing:
- ☐ contained in the international application in written form.
- ☐ filed together with the international application in computer readable form.
- ☐ furnished subsequently to this Authority in written form.
- ☐ furnished subsequently to this Authority in computer readable form.
- ☐ the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
- ☐ the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished.

2. ☐ **Certain claims were found unsearchable** (See Box I).

3. ☒ **Unity of invention is lacking** (see Box II).

**4. With regard to the title,**

- ☒ the text is approved as submitted by the applicant.
- ☐ the text has been established by this Authority to read as follows:

**5. With regard to the abstract,**

- ☒ the text is approved as submitted by the applicant.
- ☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

**6. The figure of the drawings to be published with the abstract is Figure No.**

- ☐ as suggested by the applicant.
- ☒ because the applicant failed to suggest a figure.
- ☐ because this figure better characterizes the invention.
- 5** ☐ None of the figures.

This Page Blank (uspto)

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US 00/22476

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
  
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
  
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
  
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
  
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
  
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1-10 12 19 20 24 26-36 38 45 46 50 52-55

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

**This Page Blank (uspto)**

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

1. Claims: 1-10 12 19 20 24 26-36 38 45 46 50 52-55

An internet jack for connecting an internet device to internet

2. Claim : 11 37

Ethernet hub

3. Claims: 13-17 39-43

Authentication of users

4. Claim : 18 44

Initiating passing information between device and internet

5. Claims: 21-23 47-49

Micro controller

6. Claim : 25 51

Baud rate detection

**This Page Blank (uspto)**



## INTERNATIONAL SEARCH REPORT

International Application No

T/US 00/22476

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04L12/28 H04L29/06 H04M11/06

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04M H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	WO 99 65219 A (IREADY CORP) 16 December 1999 (1999-12-16)  the whole document	1,2,4-9, 12,19, 20,24, 26-28, 30-35, 38,45, 46,50, 52-55
X	WO 99 39488 A (BRITISH TELECOMM ; FLYNN JASON STUART (GB)) 5 August 1999 (1999-08-05) page 1, line 10 -page 9, line 21 page 10, line 21 -page 15, line 30 abstract; figures 3-5,8 --- -/--	1,2,6-9, 27,28, 32-35



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&amp;" document member of the same patent family

Date of the actual completion of the international search

18 May 2001

Date of mailing of the international search report

01.08.01

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Kalabic, F

**This Page Blank (uspto)**

## INTERNATIONAL SEARCH REPORT

International Application No

T/US 00/22476

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PORTABLE COMPUTER AND COMMUNICATIONS ASSOCIATION - MODEM STANDARDS COMMITTEE: "The IP Modem Interface Standard" 6 March 1998 (1998-03-06) , IP MODEM INTERFACE STANDARD DRAFT,XX,XX, PAGE(S) 1-26 XP002120914	1,2,4-9, 12,19, 20,24, 26-28, 30-35, 38,45, 46,50, 52-55
A	the whole document	3,10,29, 36
A	--- MARGOLIN B: "SMARTER STUFF" June 1997 (1997-06) , BYTE,US,MCGRW-HILL INC. ST PETERBOROUGH, VOL. 22, NR. 6, PAGE(S) 85,87,89,91-92 XP000691560 ISSN: 0360-5280 the whole document -----	1-9

This Page Blank (uspto)

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/22476

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
W0 9965219 A	16-12-1999	AU 4435999 A CN 1305681 T EP 1086573 A	30-12-1999 25-07-2001 28-03-2001
W0 9939488 A	05-08-1999	CN 1289497 T EP 1051825 A	28-03-2001 15-11-2000

**This Page Blank (uspto)**

# INTERNATIONAL SEARCH REPORT

International Application No.

US 99/13184

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04M11/06 H04L29/06

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04M H04L G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PORTABLE COMPUTER AND COMMUNICATIONS ASSOCIATION - MODEM STANDARDS COMMITTEE: "The IP Modem Interface Standard" PCCA DRAFT, 'Online! 5 June 1998 (1998-06-05), XP002120914 Retrieved from the Internet: <URL:ftp://ftp.wrq.com/pcca/ipmd0506.pdf> 'retrieved on 1999-10-08! figure 4 page 9, line 3 -page 15, line 21 page 17, line 20 - line 28	1-4, 9, 14-16, 38, 45, 50, 55
A	--- -/--	5, 44, 46

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

29 October 1999

Date of mailing of the international search report

09/11/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Eraso Helguera, J

## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 99/13184

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 95 14356 A (QUALCOMM INC) 26 May 1995 (1995-05-26)  figures 1-3 page 5, line 10 -page 7, line 2 ---	1-4, 14-16, 38,45, 50,55
Y	PRESTON D J: "INTERNET PROTOCOLS MIGRATE TO SILICON FOR NETWORKING DEVICES" ELECTRONIC DESIGN, vol. 45, no. 8, 14 April 1997 (1997-04-14), pages 87-90, 92 - 94, XP000730016 ISSN: 0013-4872 page 87, left-hand column, paragraph 1 -page 88, left-hand column, paragraph 2 page 90, right-hand column, paragraph 3 -page 91, right-hand column, paragraph 3 ---	1-4, 14-16, 38,45, 50,55
A	FLOYD S ET AL: "LINK-SHARING AND RESOURCE MANAGEMENT MODELS FOR PACKET NETWORKS" IEEE / ACM TRANSACTIONS ON NETWORKING, vol. 3, no. 4, 1 August 1995 (1995-08-01), pages 365-386, XP000520857 ISSN: 1063-6692 page 367 -page 368 ---	6-8, 17-37, 47-49
A	HIGHLAND H J: "Historical Bits & Bytes" COMPUTERS & SECURITY INTERNATIONAL JOURNAL DEVOTED TO THE STUDY OF TECHNICAL AND FINANCIAL ASPECTS OF COMPUTER SECURITY, vol. 16, no. 5, 1 January 1997 (1997-01-01), page 387-411 XP004096186 ISSN: 0167-4048 page 392, left-hand column, paragraph 2 -page 396, left-hand column, paragraph 6 ---	10,39,51
A	MARCHIORI M: "The limits of Web metadata, and beyond" COMPUTER NETWORKS AND ISDN SYSTEMS, vol. 30, no. 1-7, 1 April 1998 (1998-04-01), page 1-9 XP004121445 ISSN: 0169-7552 page 7, left-hand column, paragraph 4 -page 8, left-hand column, paragraph 3 page 1, left-hand column, paragraph 1 -page 2, right-hand column, paragraph 3 -----	11-13, 40-43, 52-54



# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

US 99/13184

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9514356 A	26-05-1995	US 5479475 A	26-12-1995
		AU 683706 B	20-11-1997
		AU 1055895 A	06-06-1995
		BR 9405750 A	05-12-1995
		CN 1116481 A	07-02-1996
		EP 0679323 A	02-11-1995
		FI 953418 A	12-07-1995
		JP 8505995 T	25-06-1996
		US 5761204 A	02-06-1998

**This Page Blank (uspto)**

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 99/00311

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 H04L29/08 G06F15/02 H04L29/06

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 G06F H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 637 801 A (BULL SA) 8 February 1995  see abstract see page 2, line 1 - page 7, line 58 * annex 1-4 * see figures 1-3	1, 13, 17-20
A	EP 0 748 096 A (XEROX CORP) 11 December 1996 see abstract see page 1, line 1 - page 6, line 53 see figures 1,2	1, 13, 17-20
A	DE 196 18 535 A (SIEMENS AG) 24 July 1997  see the whole document	1, 13, 17-20
	--- -/-- ---	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

26 May 1999

Date of mailing of the international search report

07/06/1999

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Lievens, K

## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/GB 99/00311

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>INFORMATION SCIENCES INTITUTE, UNIVERSITY OF SOUTHERN CALIFORNIA: "TRANSMISSION CONTROL PROTOCOL" RFC793, 30 September 1981, XP002069478 . cited in the application ftp://ds.internic.net/rfc/rfc791.txt see page 8, paragraph 2.3 see page 9, paragraph 2.4 see page 10-11, paragraph 2.7 see page 44-51, paragraph 3.8 see page 52-77, paragraph 3.9 -----</p>	<p>1, 13, 17-20</p>

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/00311

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0637801 A	08-02-1995	FR 2708116 A WO 9503583 A	27-01-1995 02-02-1995
EP 0748096 A	11-12-1996	JP 9016486 A	17-01-1997
DE 19618535 A	24-07-1997	NONE	

**This Page Blank (uspto)**